



RECOMMENDED PCB LAYOUT  
PCB THICKNESS 1.6mm

TABLE 1 (SEE NOTE #3)

NO. OF POS.	PART NO.	A	B
2	Z-152-2P	2.54	—
4	Z-152-4P	5.08	2.54
6	Z-152-6P	7.62	5.08
8	Z-152-8P	10.16	7.62
10	Z-152-10P	12.70	10.16
12	Z-152-12P	15.24	12.70
14	Z-152-14P	17.78	15.24
16	Z-152-16P	20.32	17.78
18	Z-152-18P	22.86	20.32
20	Z-152-20P	25.40	22.86

- NOTE 1. CONTACT PLATING: GOLD 0.7 MICROMETERS MIN.  
ALL OVER NICKEL  
2. THIS DRAWING SHOWS Z-152-16P.  
3. Z-152-( )P IS THE SAME AS DIC-152-( )P.

③								
②			2	CONTACT	BRASS	No. OF POS.	SEE NOTE. #1	—
①			1	INSULATOR	66NYLIN	1	—	UL94V-0 BLACK

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
------	------	----	------	----------	-----	-----------	----------	-----	--------	------

DATE Jul.27.2001		SCALE 2/1		UNIT mm (INCH)		3RD. A. P		HONDA TSUSHIN KOGYO CO., LTD.		
APP. DATE&REV.										
DR.	DE.	CHK.	CHK.	APP.	NAME		MALE CONNECTOR			
N. TAOKA	R. SAITO	Y. OTANI	—	K. NARUMO	PART NO.		Z-152-( )P (DIC-152-( )P)			