



PART NO.

1. WITH KEYING
 THE UNDERLINED SECTION AT THE END OF PART NUMBER IS FILLED WITH 4 KINDS OF THE STANDARD KEY POSITION CODES.
 EXAMPLE: PCS-E (NO. OF) WKPA_B-1E

2. WITHOUT KEYING
 PCS-E (NO. OF) WKPA_B

7	KEY RIVET	BRASS	—	NICKEL PLATING	P/N: PCS-E-PK
6	ΦFLAT HEAD SCREW	STEEL	2	NICKEL PLATING	M2.5
5	COVER A	ZINC ALLOY	1	NICKEL PLATING	—
4	COVER B	ZINC ALLOY	1	NICKEL PLATING	—
3	SPRING LOCK	STAINLESS STEEL	2	—	—
2	ΦPAN HEAD SCREW	STEEL	1	NICKEL PLATING	M2.5
1	CABLE CLAMP	STAINLESS STEEL	1	—	—

PART NO.	NO. OF POS.	A DIMENSIONS	B DIMENSIONS	CABLE CHARACTERISTIC OUTSIDE DIAMETER	STANDARD KEY POSITIONS (4 TYPES)
PCS-E80WKPA-()	80	67.9	10.5x9.5	Ø9.5	1E, 2D, 4B, 5A
PCS-E68WKPA-()	68	60.3	11x10	Ø10.5	1E, 2D, 4B, 5A
PCS-E50WKPB-()	50	48.9	12x10	Ø11.5	1E, 2D, 4B, 5A
PCS-E36WKPA-()	36	40.2	10.5x9.5	Ø9.5	1D, 2C, 3B, 4A

改版 LTR.	年月日 DATE	変更者 BY	変更内容 REV. DESCRIPT	番号 No.	部品名称 PART NAME	材質 MATERIAL	個数 QTY	処理 FINISH	備考 NOTE
SEP. 30 (1994)									
製 DR.	設 DE.	計 CHK.	検 CHK.	承認 APP.	本多通信工業株式会社 HONDA TSUSHIN KOGYO CO., LTD. 名称 PCS-E TYPE CABLE COVER WITH KEYING & WITHOUT 製番 PART NO. PCS-E () WKPA _B - ()				
S. FURUSAWA	S. FURUSAWA	—	Y. HIRAI	M. TAKAHASHI					